

EXPANSION SHELL ASSEMBLY

[001] This application claims the benefit of and hereby expressly incorporates by reference U.S. Provisional Patent Application Serial No. 60/261,495, filed on January 12, 2001.

Background of the Invention

Field of the Invention

[002] The present invention relates to an improved expansion shell assembly for mine roof bolts and, more specifically, to an improved expansion shell assembly, and elements thereof, having novel features particularly adapted for the improved support and release of an expansion shell during installation of a mine roof bolt.

Description of the Art

[003] It is well known in the art of mine roof control to tension bolts anchored in bore holes drilled into the mine roof in order to reinforce the unsupported rock formation above the roof. Conventionally, a hole is drilled into the rock formation. The end of the bolt in the rock formation is anchored either by engagement of an expansion shell assembly on the end of the bolt with the rock formation, by bonding the bolt with resin to the rock formation surrounding the bore hole, or by use of both an expansion shell assembly and resin together to retain the bolt within the hole.

[004] Mechanical expansion shell assemblies for roof bolts have been used for many years in the anchorage of bolts in rock formations. An expansion shell assembly includes an expansion member such as a camming plug or

10045607 102304

tapered plug threaded onto one end of a mine roof bolt and positioned within the upper end portion of an expansion shell. The expansion shell is held in place by a support device such as a PALNUT positioned adjacent to the lower end portion of the expansion shell.

[005] During rotation of the bolt, the frictional engagement of the expansion shell with the rock formation surrounding the bore hole prevents rotation thereof. Also, by virtue of the frictional engagement between the upper end of the support device with the lower end of the expansion shell, the support device will not rotate but, upon rotation of the bolt, the support device, the expansion shell and the tapered plug move downwardly along the bolt until the support device reaches the unthreaded portion of the bolt.

[006] Continued rotation of the bolt causes the tapered plug to advance downwardly on the bolt and urges the expansion shell fingers to expand or deflect radially outwardly to grip the rock formation surrounding the bore hole. With the expansion shell engaged with the rock formation, continued rotation of the bolt causes the bolt to advance upwardly, thereby pushing or stripping the support device off the threaded portion of the bolt. Concurrently, rotation of the bolt urges a bearing plate positioned on the bolt at an end opposite the expansion shell assembly against the rock formation, putting the rock formation in compression and the bolt in tension.

[007] Current practice provides roof bolt systems using resin in conjunction with a mechanical anchor. These types of systems require a resin cartridge to be inserted in the bore hole. The bolt is then inserted in the bore hole and thrust upwardly to rupture the resin cartridge. The bolt is rotated, mixing the resin and setting the mechanical anchor. Two of the advantages of resin-using systems are a tensioned resin anchor and quick installation provided by the mechanical anchor.

[008] Examples of arrangements utilizing both an expansion shell assembly and resin to anchor a mine roof bolt in a rock formation are disclosed in U.S. Pat. Nos. 4,419,805; 4,413,930; 4,516,885 and 4,512,292, all expressly incorporated herein by reference. Other examples of both an expansion shell assembly and resin to anchor a mine roof bolt are disclosed in U.S. Pat. Nos. 3,188,815; 4,162,133; 4,655,645 and 4,664,561, all expressly incorporated herein by reference.

[009] In general, any support device of an expansion shell assembly of the prior art performs three functions during installation of the roof bolt. First, the support device maintains the expansion shell in engagement with the camming plug during insertion in the bore hole. Second, with the support device positioned adjacent the lower end of the bolt threaded portion, the support device maintains the expansion shell in a fixed axial position on the bolt thereby allowing the tapered plug to advance downwardly on the bolt and urge the expansion fingers radially outwardly to grip the rock formation. Finally, with the expansion shell engaged with the rock formation, the support device strips off the threaded portion of the bolt thereby allowing the bolt to advance upwardly and be properly tensioned.

[0010] Some early combination resin/mechanical anchor systems used a PALNUT as the support device to maintain the expansion shell in engagement with the camming plug during insertion in the bore hole. However, because of the tight clearance between the expansion shell fingers and the bore hole wall, along with the high resistance to the flow of resin caused by the anchor, the PALNUT was prone to prematurely strip off the threaded portion of the bolt. When a premature failure occurred, the expansion shell was pushed downwardly and disengaged from the camming plug. The result was an expansion shell assembly unable to engage the rock formation, a condition known in the industry as a "spinner".

10045607 102304

[0011] Manufacturers now use a hex or round jamnut of a various thickness as the support device. Although the heavier jamnut solved the premature stripping problem, it created a different problem. It has been determined that the heavier jamnut may not strip off the threaded portion. As a result, rotation of the bolt causes the expansion shell to be compressed between the camming plug and the support device. The expansion shell may become severely distorted, ripped, torn or twisted. In addition, when the jamnut fails to release, significant tension occurs in the bolt threaded portion between the camming plug and the jamnut. This tension translates into torque being measured by the roof bolt installation machine. It is common practice to install a roof bolt to a predetermined desired torque. Since significant torque is being created at the expansion shell assembly, significantly reduced torque/tension is being applied to the roof bolt. Thus, the actual tension in the bolt may be significantly less than the desired tension in the bolt.

[0012] While expansion shell assemblies for anchoring mine roof bolts in bore holes are well known, there is need to improve the operability of the support device, particularly when used with resin. The support device must have the capability to support the expansion shell during insertion in the bore hole and engagement with the bore hole wall. At the same time, the support device must have the capability to release its axially supporting engagement with the expansion shell once the expansion shell is set in the rock formation to allow for proper tensioning of the bolt while reducing or eliminating torsion and/or compression between the camming plug and the support device.

Summary of the Invention

[0013] In accordance with one aspect of the present invention, an expansion shell assembly for mine roof bolts comprises an expansion member threaded onto an associated

mine roof bolt. A support device is annularly disposed around the associated roof bolt. An expansion shell is annularly disposed around the associated roof bolt between the expansion member and the support device. The expansion shell has a base ring for engaging the support device and fingers for engaging a peripheral edge of the tapered plug. The engagement between the base ring and the support device permits axial traverse movement of the support device relative to the expansion shell for tensioning the roof bolt.

[0014] In accordance with another aspect of the present invention, a bolt and anchor assembly for securing a mine roof bolt comprises an elongated bolt and an expansion shell having an aperture for receiving the elongated bolt. An expansion member is disposed on one end of the elongated bolt for expanding the expansion shell. A shell support has a shell engaging portion radially disposed between and in contact with the elongated bolt and the expansion shell for maintaining the axial position of the expansion shell relative to the elongated bolt while the expansion member forces the shell to engage a rock formation and for moving axially relative to the expansion shell while the elongated bolt is tensioned after engagement to the rock formation.

[0015] In accordance with another aspect of the present invention, an expansion shell assembly for mine roof bolts comprises an expansion member threaded onto an associated bolt. A support device is annularly disposed around the associated bolt. A shell is annularly disposed on the bolt between the expansion member and the support device. The expansion shell has a base ring with a tapered surface for mating engagement a corresponding tapered surface of the support device and fingers for engaging the expansion member. The mating engagement allows increasing friction forces to hold the support device in a non-rotating position at a predetermined bolt torque.

10045607 102304

[0016] In accordance with yet another aspect of the present invention, a method for anchoring an elongated threaded member to a rock formation is provided. An elongated member having a threaded end portion that is to be anchored to a rock formation is provided. An expansion shell assembly is provided on the threaded end portion of the elongated member. The expansion shell assembly comprises an expansion shell, a plug for expanding the expansion shell, and a support member for supporting the expansion shell. A blind drilled hole is formed in the rock formation for the elongated member and the expansion shell assembly. The elongated member with the expansion shell assembly carried thereon is advanced into the blind drilled hole. The elongated member is rotated to effect a gripping of the rock formation by the expansion shell assembly within the blind drilled hole. The support member generally maintains engagement between the plug and the expansion shell. The elongated member is further rotated to tension the elongated member. The support member axially traverses within the expansion shell permitting the tensioning.

[0017] In accordance with still another aspect of the present invention, a method of installing a mine roof bolt assembly is provided. A mine roof bolt assembly is inserted into a hole of a rock formation. The mine roof bolt assembly comprises a mine roof bolt, an expansion member threadingly engaged to the mine roof bolt, an expansion shell, and a support. The expansion shell has fingers engaged with expansion member and a base portion engaged with the support. The hole is appropriately sized to frictionally prevent rotation of the expansion shell. The engagement of the fingers restricts rotation of the expansion member. The mine roof bolt assembly is anchored to the rock formation within the hole by rotating the mine roof bolt. Said rotation causes the support to force the expansion shell against the expansion member thereby forcing the fingers of the expansion shell to move radially

outwardly and grip the rock formation. The mine roof bolt is tensioned by continuing to rotate the mine roof bolt. Said continued rotation causes the support to forcibly move within the base portion of the expansion shell.

Brief Description of the Drawings

[0018] The invention may take form in various components and arrangements of components, and in various steps and arrangements of steps. The drawings are only for purposes of illustrating the presently preferred embodiments and are not to be construed as limiting the invention.

[0019] FIG. 1 includes an elevational view and a cross-sectional view of an expansion shell assembly having a support device on a mine roof bolt in a precisely controlled diameter arrangement in accordance with a first preferred embodiment of the present invention;

[0020] FIG. 2 includes an elevational view and a cross-sectional view of an expansion shell assembly on a mine roof bolt in a conventional shell arrangement in accordance with a second preferred embodiment of the present invention;

[0021] FIG. 3 includes an elevational view and a cross-sectional view of an expansion shell assembly on a mine roof bolt in a notched shell arrangement in accordance with a third preferred embodiment of the present invention;

[0022] FIG. 4 includes an elevational view and a cross-sectional view of an expansion shell assembly on a mine roof bolt in a split shell arrangement and an enlarged partial view of a support device taper and radius in accordance with a fourth preferred embodiment of the present invention;

[0023] FIG. 5 includes an elevational view and a cross-sectional view of the precisely controlled diameter arrangement of FIG. 1 wherein a two-piece support device is substituted for the support device of FIG. 1;

[0024] FIG. 6 includes an elevational view and a cross-sectional view of the precisely controlled diameter arrangement of FIG. 1 wherein a two-piece support device

having an antifriction washer is substituted for the support device of FIG. 1;

[0025] FIG. 7 includes an elevational view and a cross-sectional view of an expansion shell assembly having an unthreaded support device on a mine roof bolt in a precisely controlled diameter arrangement in accordance with another preferred embodiment of the present invention;

[0026] FIG. 8 includes an elevational view and a cross-sectional view of an expansion shell assembly on a mine roof bolt having a support device axially secured between rolled threads and a shoulder of the bolt in a precisely controlled diameter arrangement in accordance with another preferred embodiment of the present invention;

[0027] FIG. 9 includes an elevational view and a cross-sectional view of an expansion shell assembly on a mine roof bolt having a support device formed integrally with the bolt in a precisely controlled diameter arrangement in accordance with a ninth preferred embodiment of the present invention; and

[0028] FIG. 10 includes an elevational view and a cross-sectional view of an expansion shell assembly having a tapered shell engaged to a tapered support device on a mine roof bolt in accordance with another preferred embodiment of the present invention.

Detailed Description of the Invention

[0029] In accordance with the present invention, there is provided an expansion shell assembly for anchoring a bolt in a bore hole that includes an expansion shell, an expansion member such as a tapered camming plug, and a novel support device. The expansion shell has a circular base portion or base ring and a plurality of longitudinally extending fingers generally equally spaced from one another. Each finger is formed integral at one end portion with the circular base portion and extends upwardly therefrom to form a free end portion for outward expansion of the finger. The

404907 403904

fingers each have an inner surface for engaging the side wall of the camming plug and a ribbed outer surface for frictionally engaging the bore hole. The camming plug has a threaded axial bore for engaging the end of the bolt, an upper end portion, a lower end portion, and a surrounding side wall tapering inwardly from said upper end portion to said lower end portion. The inner surface of the fingers abuts the plug side wall. The novel support device in general consists of a ring-like structure with an axial bore that may or may not be threaded, a lower end portion, an upper end portion whose outer diameter is less than the lower end portion, and an outer surface of a predetermined transition configuration.

[0030] Unlike prior art where the support device such as a PALNUT or a jamnut had to be forced axially down the bolt by the expansion shell during tensioning of the bolt, this support device cooperates with the expansion shell base portion in one of two general ways. In one way, as illustrated in at least Figs. 1 through 9, the upper end portion of the support device cooperates with the expansion shell base portion to cause the expansion shell base portion to diametrically expand and/or fracture and, at a predetermined axial force, allow the support device to traverse axially therethrough during tensioning of the bolt. In another way, as illustrated in Fig. 10, the upper end portion of the support device cooperates with the expansion shell base portion to cause the support device to be held in a fixed, non-rotating position thereby allowing the bolt to advance upwardly at a predetermined torque.

[0031] There are several ways to practice the invention as discussed in detail below. However, it should be understood by one skilled in the art that the invention may be practiced otherwise than as specifically illustrated and described below. It should also be noted that the invention may be practiced with the following U.S. Patents: 4,413,930; 4,419,805; 4,516,885; 4,518,292; 4,664,561; 4,678,374;

4,679,966; 4,764,055; 4,904,123; 4,913,593; 4,969,778;
5,011,337; 5,244,314, all expressly incorporated herein by
reference.

[0032] Referring now to the drawings wherein like reference characters represent like elements, with reference to Fig. 1, an expansion shell assembly is shown in a precisely controlled diameter arrangement. The expansion shell assembly connects to a mine roof bolt 12 on a threaded end 14 thereof and comprises an expansion shell 16, a tapered camming plug 18, and a support device 20 according to a first preferred embodiment of the present invention.

[0033] The expansion shell 16 has a circular base portion 22 and a plurality of longitudinally extending fingers 24 generally spaced apart from one another. The inner surface or inner diameter of the circular base portion 22 is a precisely controlled diameter relative to an outside diameter of the support device 20 creating a controlled interference fit such as a 0.030 inch diametral fit. That is, the inner diameter of the base portion 22 is 0.030 inches smaller than the outside diameter of the support device 20. This is in contrast to conventional prior art expansion shells which are often formed by casting resulting in significantly higher tolerances. The controlled relationship between the controlled diameter and the outer diameter of the support device 20 facilitates fracture and/or expansion of the base portion 22 during installation as will be discussed in more detail below. Each of the fingers 24 is formed integral at one end with the circular base portion 22 and extends upwardly therefrom to form a free end portion for outward expansion of the finger 24. The fingers 24 each have an inner surface for engaging one of a plurality of flat side walls 26 of the camming plug 18 and an outer ribbed surface 28 for frictionally engaging a bore hole (not shown) formed within a rock formation.

[0034] The tapered camming plug 18 has a threaded axial bore for engaging the threaded end portion 14 of the bolt

12, an upper end 30, a lower end 32, and the surrounding flat side walls 26 tapering inwardly from the upper end 30 to the lower end 32. Each of the plurality of side walls 26 abuts the inner surface of one of the fingers 24 of the expansion shell 16.

[0035] The support device 20 has a threaded axial bore 34 for threaded engagement with the bolt 12, a lower end 36, an upper end 38 whose outer diameter is less than the lower end 36, and a surrounding side wall 40 that transitions outwardly from the upper end 38 to the lower end 36. The outer transition surface 40 has an outwardly tapered portion 42 beginning at the upper end, a transition radius portion 44 (such as about 0.030 inches), and a straight portion 46 that is parallel to the axial bore ending at the lower end 36. The straight portion 46 defines the outside diameter of the support device 20 which determines the size of the controlled diameter of the base portion 22. In the precisely controlled diameter arrangement illustrated, the tapered portion 42 is approximately sixty degrees relative to a vertical axis of the bolt 12. Of course, other taper angles can be used to achieve the same result and all such configurations are to be considered within the scope of the present invention.

[0036] For installation in the bore hole, the support device 20, the expansion shell 16, and the camming plug 18 are positioned on the threaded end portion 14 of the mine roof bolt 12 as illustrated. More specifically, the support device 20 is threaded onto the bolt 12 to a position located slightly above an unthreaded portion 48 as illustrated. Alternatively, the support device 20 can be threaded onto the bolt 12 until it reaches or is adjacent the unthreaded portion 48. The expansion shell 16 and the camming plug 18 are then positioned on the bolt 12 such that the circular base portion 22 overlaps the tapered surface of the support device 20 as shown. As can readily be seen, the expansion shell 16 is sandwiched between the camming plug 18 and the

support device 20. The expansion shell assembly 10 and the bolt 12 are then inserted in the bore hole. In this instance, the expansion shell 16 and roof bolt 12 are utilized without resin bonding. However, it will be appreciated that the expansion shell assembly of the present invention can also be utilized with resin.

[0037] For resin bonding, a resin cartridge (not shown) is positioned within the bore hole above the expansion shell assembly. The expansion shell assembly, attached to the bolt 12 as described above, is thrust upwardly in the bore hole to rupture the resin cartridge. During insertion in the bore hole, the expansion shell fingers 24 are held in engagement with the camming plug 18 by the support device 20. In particular, the outwardly tapered portion of the support device 20 cooperates with the circular base portion 22 of the expansion shell 16 thereby maintaining the shell fingers 24 in engagement with the camming plug 18.

[0038] As the roof bolt 12 is rotated, the contents of the resin cartridge are mixed together. Also, by virtue of the frictional engagement of the expansion shell 16 with the rock formation surrounding the bore hole, the expansion shell 16, the camming plug 18, and the support device 20 move downwardly along the bolt 12 until the support device 20 reaches a thread runout or unthreaded portion 48 of the bolt 12. Of course, if the support device 20 is initially positioned adjacent the unthreaded portion 48, this step will not occur.

[0039] In either case, with the support device 20 located at the thread runout 48 and maintaining the expansion shell 16 at a fixed axial position on the bolt 12, continued rotation of the bolt 12 allows the tapered plug 18 to advance downwardly on the bolt 12 thereby urging the expansion fingers 24 radially outwardly to engage the rock formation. More particularly, the outwardly tapered portion 42 of the support device 20 cooperates with the circular base portion 22 of the expansion shell 16 thereby

maintaining the expansion shell 16 in a fixed axial position on the bolt 12.

[0040] Finally, with the expansion shell 16 engaged with the rock formation, continued rotation of the bolt 12 increases the axial force between the expansion shell 16 and the support device 20. By virtue of the outwardly tapered portion 42 of the support device 20, the increasing axial force is accompanied by an increasing radial force which urges the circular base portion 22 of the expansion shell 16 to increase in diameter. Thus, because of the tapered portion 42 and/or the precisely controlled diameter of the base portion 22, the circular base portion 22 of the expansion shell 16 diametrically expands at a predetermined axial force, such as approximately 4,300 lbs., and a corresponding bolt torque, such as a torque of less than approximately 100 ft. lbs., sufficient enough to allow the support device 20 to traverse axially within and through the base portion 22 of the expansion shell 16 thereby allowing the bolt 12 to advance upwardly and be properly tensioned.

[0041] More specifically, a reference point or datum 50 on the support device 20 converges with a reference point or datum 52 on the circular base portion 22 after or while the diametric expansion of base portion 22 occurs at the predetermined force and corresponding bolt torque. That is, a distance D between the datums 50 and 52 is reduced at the predetermined force and corresponding bolt torque. The relative movement between the support device 20 and the circular base portion 22 is unlike the prior art where the circular base portion and the support device move in tandem down the mine roof bolt when the support device strips off the threaded portion of the bolt. It should be appreciated that in the embodiment illustrated the support device 20 axially traverses through the circular base portion 22 but other variations are possible, such as having the support device axially traverse annularly around the circular base portion, and all such variations are to be considered within